


# Quectel LG580P (03)

#### Full-Constellations and Multi-Bands **High-Precision GNSS Module**



LG580P (03) is a full-constellations, multi-bands GNSS module with 1040 tracking channels, which supports concurrent reception of GPS, GLONASS, Galileo, BDS, QZSS, and NavIC constellations, as well as multiple SBAS systems (WAAS, EGNOS, BDSBAS, MSAS, GAGAN, KASS, ASECNA, SouthPAN, and SDCM).

The built-in professional-grade interference signal detection and elimination algorithms effectively mitigate multiple narrow-band interferences, which significantly improves signal reception performance, particularly in complex electromagnetic environments. In addition, LG580P (03) supports multi-band signals L1, L2, L5, L6 and features builtin RTK + Heading algorithms, significantly enhancing robustness in challenging environments such as dense foliage canopy and urban canyons, enabling high-precision positioning capabilities.

LG580P (03) supports integrity information detection functions such as protection level to assist control decisionmaking in applications like autonomous navigation. It also features on-chip memory ECC verification and Secure Boot loading mechanisms, providing additional firmware security. In addition, it offers versatile peripheral interfaces including UART, SPI\*, I2C\*, and CAN\* to meet diverse application requirements.

With high precision, low power consumption and a high positioning and heading update rate of up to 20 Hz, LG580P (03) is an ideal choice for high-precision navigation applications, such as intelligent robots, precision agriculture, ADAS, and autonomous driving.



### **Key Features**

- Concurrent reception of multi-constellation signals: GPS, GLONASS, Galileo, BDS, QZSS, NavIC and SBAS
- ✓ Multi-band GNSS signals: L1, L2, L5 and L6
- ✓ High positioning and heading update rate of up to 20 Hz
- Built-in professional-grade NIC anti-jamming unit to suppress multiple narrow-band interferences
- Abundant interfaces: UART, SPI\*, I2C\* and CAN\*
- AGNSS\* technology



Multi-constellation



Multi-band



Low Power Consumption



-160 dBm



Tracking Sensitivity: Operating Temperature Range: -40 °C to +85 °C



Anti-iamming



RoHS Compliant



Ultracompact Size



AGNSS Technology

## Quectel LG580P (03)

| GNSS Module  | LG580P (03)  |
|--|--|
| Dimensions   | 21.0 mm × 16.0 mm × 2.7 mm                                     |
| Weight   | Approx. 1.4 g  |
| Femperature Range  |  |
| Operating Temperature  | -40 °C to +85 °C   |
| Storage Temperature  | -40 °C to +95 °C   |
| GNSS Features  |  |
|  | GPS: L1 C/A, L2C, L5   |
|  | GLONASS: L1, L2  |
| Supported Bands  | Galileo: E1, E5a, E5b, E6                                      |
| (Primary and Secondary Antennas <sup>®</sup> )   | BDS: B1I, B1C, B2I, B2a, B2b, B3I                              |
|  | QZSS: L1 C/A, L2C, L5, L6                                      |
|  | NavIC: L5  |
| Default Constellations   | GPS + GLONASS + Galileo + BDS + QZSS + NavIC                   |
| Number of Tracking Channels  | 1040   |
| SBAS   | WAAS, EGNOS, BDSBAS, MSAS, GAGAN, KASS, ASECNA, SouthPAN, SDCM |
| unction  | RTK + Heading  |
| Horizontal Position Accuracy   | Autonomous: 1 m <sup>②</sup> RTK: 0.8 cm + 1 ppm <sup>③</sup>  |
|  | Autonomous: 1.5 m <sup>2</sup>                                 |
| Vertical Position Accuracy   | RTK: 1.5 cm + 1 ppm <sup>3</sup>                               |
| /elocity Accuracy <sup>④</sup>   | Without Aid: 0.03 m/s  |
| Perocity Accuracy ♥  LPPS Signal Accuracy (1σ) ®   | 5 ns   |
| RTK Convergence Time <sup>③</sup>  | 5 is 5 s   |
| Heading Accuracy <sup>⑤</sup>  | 0.1°   |
| neading Accuracy   | Cold Start: 28 s   |
| TTFF (without AGNSS*)®  Sensitivity (@ Default Constellations)®  Dynamic Performance®  Update Rate | Warm Start: 28 s   |
|  | Hot Start: 1.8 s   |
|  | Acquisition: -145 dBm  |
|  | Tracking: -160 dBm   |
|  | Reacquisition: -155 dBm  |
|  | Maximum Altitude: 10000 m                                      |
|  | Maximum Velocity: 490 m/s                                      |
|  | Maximum Acceleration: 4g                                       |
|  | Default: 10 Hz   |
|  | Max.: 20 Hz  |
| Certifications   |  |
| Regulatory   | Europe: CE*  |
| Others   | RoHS   |
| nterfaces  |  |
|  | ×3   |
| UART   | Adjustable: 9600-3000000 bps                                   |
|  | Default: 460800 bps  |
| I2C*   | ×1   |
|  | Max. 400 kbps  |
| SPI*   | ×1   |
|  | Recommended baud rate range: 1-3 Mbps                          |
| CAN*   | × 1 (Multiplexed from UART3)                                   |
| Protocols  |  |
| Protocol   | NMEA 0183, RTCM 3.x and QGC                                    |
| Antenna Interface  |  |
| Antenna Type   | External active antenna®                                       |
| Antenna Power Supply   | External   |
| Electrical Characteristics   | 2.0.2.CV Tun. 2.2.V  |
| Supply Voltage Range   | 3. 0–3.6 V, Typ. 3.3 V   |
| /O Voltage   | Typ. 3.3 V   |
|  | Normal Operation:  |
| Current Consumption <sup>④</sup>   | 98 mA (323.4 mW) @ Acquisition                                 |
| (@ 3.3 V, Default Constellations)  | 116 mA (382.8 mW) @ Tracking                                   |
| ,,   | Power Saving Mode:   |
|  | 18 μA(59.4 μW)@ Backup Mode                                    |

- NOTE:

  \* Under development/ in progress.

  ① The secondary antenna does not support GLONASS L1 and L2, Galileo E6, BDS B3I and QZSS L6.

  ② Tested under CEP 50% in static open-sky conditions over 24 hours.

  ③ Tested under CEP 50% in open-sky conditions voin given precision active GNSS antennas, with baseline lengths maintained below 1 km.

  ⑤ Tested at 25 °C ambient temperature under typical operating voltage, with satellite signals set to -130 dBm using test instruments.

  ⑥ Standard deviation value obtained under static conditions in open-sky conditions with a baseline length of 1 meter.

  ⑥ Tested at 25 °C under typical operating voltage in open-sky conditions.

  ⑦ Tested using two external LNAs (18.5 dB gain, 0.85 dB noise figure), with minimum tracked satellites: GPS L1 + L5 ≥ 12, BDS B1I + B2a ≥ 10, Galileo E1 + E5a ≥ 10.

  ◎ To mittigate the impact of out-of-band interference on GNSS module performance, active antennas with the SAW filter placed in front of the LNA must be used. DO NOT use active antennas where the LNA is placed in front of the SAW filter.

